



Main

Product or component type	Circuit breaker
Range of product	Powerlink
Circuit breaker type	ECB-G3
Circuit breaker application	HACR rated Switching Duty rated HID rated
Accessory / separate part type	Motor for circuit-breaker 24 V DC
Trip unit technology	Thermal-magnetic standard LI

Complementary

Line Rated Current	20 A
Product certifications	CSA UL listed
System Voltage	480Y/277 V AC
Mounting mode	Bolt-on
Poles description	1P
Breaking capacity	65 kA at 120 V AC 14 kA at 277 V AC
Number of spaces required	1
Electrical connection	Bolted connection
AWG gauge	AWG 12...AWG 8 (aluminium) AWG 10...AWG 8 (copper)

Environment

ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1423 - Schneider Electric declaration of conformity	Compliant - since 1423 - Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.