



The TRILIGHT SPIRAL LAMP provides three intensities of light (13, 20 and 25 watts), which are equivalent to incandescent lamps of 60, 75 and 100 watts.

Operating temperature:
-23°C/-10°F to 55°C/131°F

The BUG LIGHT is best used in outdoor patio/garden fixtures around seating and barbecue areas. Can also be used as other regular or coloured spirals.

Operating temperature:
-23°C/-10°F to 55°C/131°F

HIGH POWER FACTOR lamps are more efficient because they have a low total harmonic distortion (THD). Suitable for use in totally enclosed fixtures.

Operating temperature:
-29°C/-20°F to 71°C/160°F

Trilight



Bug Light



High Power Factor



Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
High Power Factor		11 W: MOL : 4 1/4 in. (108 mm) 20 W: MOL : 5 1/8 in. (130 mm) 23 W: MOL : 5 1/2 in. (130 mm)	Dia. : 2 3/4 in. (60 mm) Dia. : 2 5/8 in. (58 mm) Dia. : 2 5/8 in. (58 mm)						
58393	CF11/HPF/27K/SPIRAL/E26/STD	11	E26	2 700	82	10 000	500	48	40
58404	CF20/HPF/27K/SPIRAL/E26/STD	20	E26	2 700	82	10 000	1 200	48	75
57862	CF23/HPF/27K/SPIRAL/E26/STD	23	E26	2 700	82	10 000	1 400	48	100
Trilight		MOL : 6 1/16 in. (154 mm)	Dia. : 2 1/4 in. (57 mm)						
58959	CF13/20/25/27K/SPIRAL/E26/STD	13 20 25	E26	2 700	80	8 000	900 1 200 1 550	48	60 75 100
Bug Light		MOL : 4 3/32 in. (112 mm)	Dia. : 1 25/32 in. (45 mm)						
59162	CF13/Y/BG/SPIRALE/E26/STD	13	E26	Yellow	N/A	10 000	N/A	48	60



Specialty Lamps