

T2 Spiral



MOL : 4 11/32 in. (110 mm)
Ø 2 5/32 in. (65 mm)

18 W



MOL : 5 1/16 in. (129 mm)
Ø 2 1/8 in. (54 mm)

26 W

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
18 watts									
62832 ¹	CF18/T2/27K/SPIRAL/E26/STD	18	E26	2 700	1 250	12 000	82	75	6/48
62833 ¹	CF18/T2/30K/SPIRAL/E26/STD	18	E26	3 000	1 250	12 000	82	75	6/48
62834 ¹	CF18/T2/35K/SPIRAL/E26/STD	18	E26	3 500	1 250	12 000	82	75	6/48
26 watts									
63388 ¹	CF26/T2/27K/SPIRAL/E26/STD	26	E26	2 700	1 750	10 000	82	100	6/48
63389 ¹	CF26/T2/30K/SPIRAL/E26/STD	26	E26	3 000	1 750	10 000	82	100	6/48
63391 ¹	CF26/T2/41K/SPIRAL/E26/STD	26	E26	4 100	1 750	10 000	82	100	6/48
63392 ¹	CF26/T2/50K/SPIRAL/E26/STD	26	E26	5 000	1 750	10 000	82	100	6/48

GU24 Based



13 W: MOL : 3 5/8 in. (92 mm)
Ø 1 13/16 in. (46 mm)
18 W: MOL : 4 13/32 in. (112 mm)
Ø 1 1/8 in. (54 mm)
23 W: MOL : 4 13/32 in. (112 mm)
Ø 1 1/8 in. (54 mm)

Spiral (GU24)



23 W: MOL : 4 27/32 in. (123 mm)
Ø 2 1/8 in. (54 mm)

Dimmable Spiral (GU24)

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
Spiral									
61843	CF13/T2/35K/SPIRAL/GU24/STD	13	GU24	3 500	880	10 000	82	60	6/48
61845	CF18/T2/27K/SPIRAL/GU24/STD	18	GU24	2 700	1 150	10 000	82	75	6/48
61846	CF23/T2/27K/SPIRAL/GU24/STD	23	GU24	2 700	1 600	10 000	82	100	6/48
61847	CF23/T2/41K/SPIRAL/GU24/STD	23	GU24	4 100	1 600	10 000	82	100	6/48
Spiral - Dimmable									
60921 ²	CF23/D/27K/SPIRAL/GU24/STD	23	GU24	2 700	1 500	10 000	82	100	6/48



dimmable



outdoor



CERTIFIED

High Wattage Spiral



Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
32 watts									
60932	CF32/27K/SPIRAL/E26/STD	32	E26	2 700	2 000	10 000	82	120	6/48
58412	CF32/65K/SPIRAL/E26/STD	32	E26	6 500	2 100	10 000	82	120	6/48
40 watts									
60940	CF40/35K/SPIRAL/E26/STD	40	E26	3 500	2 600	10 000	82	150	6/48
60942	CF40/50K/SPIRAL/E26/STD	40	E26	5 000	2 600	10 000	82	150	6/48
60943	CF40/65K/SPIRAL/E26/STD	40	E26	6 500	2 600	10 000	82	150	6/48
55 watts									
60922	CFL55/27K/SPIRAL/E26/STD	55	E26	2 700	3 700	10 000	82	300	6/48
60923	CFL55/50K/SPIRAL/E26/STD	55	E26	5 000	3 700	10 000	82	300	6/48
65 watts									
60924	CFL65/27K/SPIRAL/E26/STD	65	E26	2 700	4 300	10 000	82	300	6/48
60925	CFL65/50K/SPIRAL/E26/STD	65	E26	5 000	4 300	10 000	82	300	6/48
85 watts									
60926	CFL85/27K/SPIRAL/E26/STD	85	E26	2 700	5 400	10 000	82	350	6/12
60927	CFL85/50K/SPIRAL/E26/STD	85	E26	5 000	5 400	10 000	82	350	6/12
105 watts									
60929	CFL105/50K/SPIRAL/E39/STD	105	E39	5 000	6 500	10 000	82	400	6/12

