

## Class 2 Drivers with Constant Power Output Tuning

P/N	Output			Input Voltage	Control	Case Drawing
	Current (mA)	Max Power (W)	Voltage			
D700C30UNVTW-C	700	30	15V to 44V @ 0.700A 15V to 56V @ 0.530A	120-277	Tuning, 0-10V	C
D700C30347TW-C	700	30	15V to 44V @ 0.700A 15V to 56V @ 0.530A	347	Tuning, 0-10V	C
D10CC30UNVTW-C	1050	30	15V to 30V @ 1.050A 15V to 56V @ 0.530A	120-277	Tuning, 0-10V	C
D10CC30347TW-C	1050	30	15V to 30V @ 1.050A 15V to 56V @ 0.530A	347	Tuning, 0-10V	C
D10CC55UNVTW-C	1050	55	19V to 53V @ 1.05A 19V to 56V @ 0.98A	120-277	Tuning, 0-10V	C
D10CC55347TW-C	1050	55	19V to 53V @ 1.05A 19V to 56V @ 0.98A	347	Tuning, 0-10V	C
D15CC55UNVTW-C	1500	55	13V to 37V @ 1.50A 13V to 56V @ 0.98A	120-277	Tuning, 0-10V	C
D15CC55347TW-C	1500	55	13V to 37V @ 1.50A 13V to 56V @ 0.98A	347	Tuning, 0-10V	C
D21CC80UNVTW-D	2100	80	15V to 38V @ 2.1A 15V to 56V @ 1.4A	120-277	Tuning, 0-10V	D
D21CC80347TW-D	2100	80	15V to 38V @ 2.1A 15V to 56V @ 1.4A	347	Tuning, 0-10V	D

## Mid and Low-Wattage Class 2 Drivers with Output Tuning

P/N	Output			Input Voltage	Control	Case Drawing
	Current (mA)	Max Power (W)	Voltage			
D700C30UNVTZ-C	700	30	15-44V	120-277	Tuning, 0-10V	C
D10CC30UNVTZ-C	1050	30	15-30V	120-277	Tuning, 0-10V	C
D10CC55UNVTZ-C	1050	55	19-53V	120-277	Tuning, 0-10V	C
D15CC55UNVTZ-C	1500	55	13-37V	120-277	Tuning, 0-10V	C
D21CC80UNVTZ-D	2100	80	17-38V	120-277	Tuning, 0-10V	D
D23CC90UNVT-F	2300	90	18-40V	120-277	Tuning, 0-10V	F

- EVERLINE® drivers for mid-wattage applications are ideal for high lumen downlights, high bay fixtures, and outdoor luminaire applications.
- Drivers with tuning provide the ability to set the output current at levels lower than its full output rating, while maintaining the same voltage range. This new tuned level becomes the full light output for dimming control.

Mid-Wattage Family



Case	Length	Width	Height	Mounting Length	Lead Exit
A	9.50"	1.70"	1.18"	8.89"	Side
C	14.25"	1.18"	1.00"	13.75"	Side
D	16.88"	1.25"	1.00"	16.28"	Side
F	9.50"	2.40"	1.55"	8.89"	Side
FJ	9.50"	2.40"	1.55"	#8/32 Studs 2.0"	Bottom
J	3.74"	1.57"	1.00"	3.35" x 1.18"	Side
JF	4.67"	1.30"	1.19"	4.39" x 0.96"	Side
MS	3.27"	3.00"	1.56"	#8/32 Studs 2.0"	Bottom
MSF	4.00"	3.00"	1.56"	3.62" x 2.44"	Side
VF	5.43"	3.62"	1.57"	5.16" x 2.84"	Side
VN	5.02"	3.62"	1.57"	No Feet	Side
VJ	5.02"	3.62"	1.57"	#8/32 Studs 2.0"	Bottom



**A-Can**



**C-Can**



**D-Can**



**F-Can**



**FJ-Can**



**J-Can**




**JF-Can**



**MS-Can**



**MSF-Can**



**VF, VN, VJ-Can**  
(VN-Can Shown)